



BS-2190A Inverted Biological Microscope



BS-2190A

BS-2190AF

Introduction

BS-2190A series Inverted Biological Microscopes are specially designed for observation of cell tissues culture and can be used to observe cell growth processes, tissue contours and internal structures. Optional professional fluorescence attachment can be used to observe autofluorescence phenomena in cells, fluorescence transfection, protein transfer and other fluorescence phenomena of biological cells.

With innovative infinite optical system and ergonomic design, the microscopes have excellent optical performance and easy to operate features. The microscopes have smooth and comfortable operation, they could be used for medical and health units, universities, research institutes to observe cultured living cells and tissues.

Feature

- 1. Color corrected infinite optical system, excellent optical performance and great images.
- 2. Application of high-contrast and low chromatic phase contrast observation, access to detailed examination of internal structure of the cells.
- 3. Supply long working distance and high N.A. objectives to get the flat and clear images.
- 4. Long working distance condenser has capacity to use revolution bottle and suitable for many sample petridishes.
- 5. Well-designed body structure, steady and reliable and better anti-vibration performance.
- 6. Low position coaxial coarse and fine adjustment, ergonomic design.
- 7. Professional vertical fluorescent technology, to get clear and bright fluorescent images.
- 8. Long working distance infinite plan achromatic objective, phase contrast objective and fluorescent objectives are available.







Long working distance infinite plan and phase contrast achromatic objective



Long working distance fluorescent infinite plan and semi-APO phase contrast objective





Application

BS-2190A series inverted microscopes can be used by medical and health units, universities, research institutes for observations of micro-organisms, cells, bacteria and tissue cultivation. They can be used for continuous observation of process of cells, bacteria grow and divide in the culture medium. Videos and images can be taken during the process. These microscopes are widely used in cytology, parasitology, oncology, immunology, genetic engineering, industrial microbiology, botany and other fields.

Specification

Item	Specification		BS-2190A	BS-2190AF
Optical System	Infinite Optical System, Tube Length 180mm, Parfocal Distance 45mm		•	•
Viewing Head	45° inclined Seidentopf trinocular head, diopter adjustment on left eyepiece tube, inter-pupillary range: 50-76mm, eyepiece: trinocular=80:20,100:0, Eyepiece Tube Diameter 30mm		•	•
	45° inclined Seidentopf binocular head, diopter adjustment on left eyepiece tube, inter-pupillary range: 50-76mm, Eyepiece Tube Diameter 30mm		0	0
	High eye-point wide field plan eyepiece PL10×/22mm		•	•
Eyepiece	High eye-point wide field plan eyepiece PL10×/22mm with eyepiece micrometer		0	0
	High eye-point wide field plan eyepiece PL15×/16mm		0	0
Objective (Parfocal distance 45mm, RMS (20.32x 0.706mm))	Infinite LWD Plan Achromatic Objective	4× /0.13, WD=10.75mm	0	0
		10×/0.25, WD=7.45mm	0	0
		20×/0.40, WD=6.92mm	0	0
		40×/0.65, WD=2.74mm	0	0
		60×/0.70, WD=1.28mm	0	0
	Infinite LWD Plan Phase Contrast Achromatic Objective	PH4×/0.13, WD=10.75mm	•	0
		PH10×/0.25, WD=7.45mm	•	•
		PH20×/0.40, WD=6.92mm	•	0
		PH40×/0.65, WD=2.74mm	•	0
	Infinite LWD Plan Fluorescent Objective	Fluor 4×/0.13, WD=18.95mm	0	•
		Fluor 10×/0.30, WD=7.27mm	0	•
		Fluor 20×/0.45, WD=6.03mm	0	0
		Fluor 40×/0.65, WD=1.79mm	0	0
		Fluor 60×/0.75, WD=1.28mm	0	0
	Infinite LWD Semi-APO Plan Phase Contrast and	FL PH20×/0.45, WD=6.12mm	0	•
	Fluorescent Objective	FL PH40×/0.65, WD=1.79mm	0	•
	Centering Objective	Fluorescent centering objective	0	•
Nosepiece	Inward Quintuple Nosepiece		•	•
	Inward Quadruple Nosepiece		0	0
Condenser	N.A. 0.3 LWD Condenser, Working Distance 72mm, detachable			•





Telescope	Centering Telescope(Φ30mm): used to adjust the center of phase annulus	•	•
Phase Annulus	4×, 10×-20×, 40× Phase Annulus Plate (center adjustable)	•	•
Stage	Stage 160 (X)×250(Y) mm fixed stage with glass insert plate (Φ110mm)	•	•
	Attachable Mechanical Stage, X-Y Coaxial Control, Moving Rang: 120(X)×80(Y) mm	0	•
	Extension stage, used to extend the stage		•
	Terasaki Holder: used for Φ35mm Petri Dish Holder and Φ65mm petri dishes	0	_
	(Ф65mm and 56×81.5mm)		•
	Glass Slide Holder and Petri Dish Holder (Φ54mm and 26.5×76.5mm)	0	•
	Petri Dish Holder Φ35mm	•	•
	Metal plate Φ12mm (water drop type)		0
	Metal plate Φ25mm (water drop type)		0
	Metal plate (kidney type)	0	•
Focusing	Coaxial Coarse and Fine Adjustment, tension adjustment knob, Fine Division		
	0.002mm, Fine stroke 0.2mm per rotation, Coarse stroke 37.5mm per rotation.		•
	Moving Range: 9mm, focal plane up 6.5mm, down 2.5mm		
Transmitted	6V/30W long working life halogen lamp(Philips), Pre-centered, Brightness		
Illumination	Adjustable	•	•
	EPI fluorescent attachment, 3-position for fluorescent filters, 1-position for bright		
	field	0	•
	Lamp house for mercury lamp, center adjustable	0	•
	Power supply box for mercury lamp, input voltage 100-240V AC	0	•
EPI-Fluorescent	100W mercury (ORSAM)	0	•
Attachment	Eyes Protective Plate, used to prevent harm from fluorescent light	0	•
	B1 fluorescent filter (band-pass type)		•
	G1 fluorescent filter (band-pass type)	0	•
	UV1 fluorescent filter (band-pass type)		•
	V1 fluorescent filter (band-pass type)	0	0
Filters for	Green filter (Φ45mm)	•	•
Transmitted	Blue filter (Φ45mm), only used for halogen illumination		•
Illumination	IR filter (Ф45mm)		0
-	ND25 filter (25% light transmittance)	0	•
ND Filter	ND50 filter (50% light transmittance)	0	0
	0.35× C-mount Adapter (focus adjustable, could not work with fluorescent		
	microscope)	0	
C-mount Adapter	0.5× C-mount Adapter (focus adjustable)	0	0
	0.65× C-mount Adapter (focus adjustable)	0	0
	1× C-mount Adapter (focus adjustable)		0
Trinocular Tube	Trinocular Tube Φ23.2mm, used to connect camera	0	0
	Allen wrench, M3 and M4, 1pc each	•	•
Other Accessories	Fuse, T250V500mA	•	•
	Dust cover	_	•





Packing	1 cartons/set, Packing Size: 80cm×57cm×31cm, Gross Weight: 13kgs, Net Weight: 9kgs	•	
	1 cartons/set, Packing Size: 80cm×57cm×60cm, Gross Weight: 26kgs, Net Weight:		
	20kgs		•

Note: ● Standard Outfit, ○ Optional

Sample Images







