

# Mixing & Heating



## 10L Mini Overhead Stirrer

OS10-mini



Model	OS10-mini
Max. stirring quantity [H <sub>2</sub> O]	10L
Speed range[RPM]	100-2500
Speed display	Scale
Speed display resolution[RPM]	Scale
Speed increase/decrease[RPM]	Scale
Viscosity max. [ mPas]	10000
Motor type	De brush motor
Max. torque	20N · cm
Overload protection	Automatic stop
Chuck clamp range diameter[ mm]	0.5-10
Protection class	IP21
Voltage.Frequency	100-240v,50/60 Hz
Input power[W]	45
output power[W]	35
power[W]	50
Dimension [W×H×D ][ mm]	373x238x623
Weight[kg]	5.8
Permissible ambient temperature and humidity	5-40° C, 80%RH

## 10L OLED Digital Overhead Stirrer

OS10-PRO

Model	OS10-PRO
Max. stirring quantity [H <sub>2</sub> O]	10L
Speed range[RPM]	200-2500
Speed display	OLED
Speed display resolution[RPM]	±1
Speed increase/decrease[RPM]	50
Viscosity max. [ mPas]	10000
Motor type	De brush motor
Max. torque	20N · cm
Overload protection	Automatic stop
Chuck clamp range diameter[ mm]	0.5-10
Protection class	IP21
Voltage.Frequency	100-240v,50/60 Hz
Input power[W]	45
output power[W]	35
power[W]	50
Dimension [W×H×D ][ mm]	373 X 238 X 623
Weight[kg]	4.8
Permissible ambient temperature and humidity	5-40° C, 80%RH



03

02