

# Centrifuge



# Low Speed PRP Centrifuge

WTLC-0506

## Features

- Speed range from 300-5000 rpm
- Set and displayed by RPM or G-force
- Two programs P1/P2, easy to start the procedure by one key
- Two deceleration speeds setting to meet different requirements
- Easy-to-read LCD display and sound alert
- Automatic lid-lock release after running
- Maintenance-free brushless DC motor



| Specifications            | WTLC-0506  |
|---------------------------|--|
| Speed Range               | 300-5000rpm, increment: 10rpm                                    |
| Max. RCF                  | 2350xg, increment: 10g   |
| Speed accuracy            | ±20rpm   |
| Rotor capacity            | 6x15ml/10mL/7mL/1.5-5mL  |
| Run Time                  | 30sec-99min, HD(continuous running)                              |
| Display                   | LCD  |
| Programs Memory           | 2  |
| Acceleration/Deceleration | 1 ↑ 2 ↓  |
| Safety Devices            | Door interlock, Overspeed detector; Automatic internal diagnosis |
| Motor                     | Brushless DC motor   |
| Power                     | Single-phase,<br>110V-240V, 50Hz/60Hz, 70W                       |
| Dimension [W×D×H]         | 300×240×180mm  |
| Weight                    | 5.2kg  |