

COMBINED REFRIGERATOR AND FREEZER

(2~8°C, -10~-26°C) / (2~8°C, -10~-40°C)



BNCRF-26U208



BNCRF-26U260



BNCRF-26U265



BNCRF-40U288



BNCRF-26U289



BNCRF-40U289



BNCRF-26U450



BNCRF-26U519



BNCRF-40U450



BNCRF-40U519



Specifications

	Model	BNCRF-26U208	BNCRF-26U260	BNCRF-26U265	BNCRF-40U288
	Cabinet type	Upright	Upright	Upright	Upright
	Cooling method	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling
	Defrost	Manual	Manual	Manual	Manual
	Refrigerant	R134a	R600a	R134a	R:R134a ,F:R404a
Technical Data	Power consumption(kWh/24h)	0.41kwh	1.54kWh	0.49kwh	2.12kwh
	Noise (db)	≤55db		≤55db	≤55db
	Ambient temperature (°C)	16~32°C	16~32°C	16~32°C	16~32°C
	Temperature range (°C)	2~8°C,-10~-26°C	2~8°C,-10~-26°C	2~8°C,-15~-26°C	2~8°C,-20~-40°C
	Temperature controller	Microprocessor	Microprocessor	Microprocessor	Microprocessor
	Display	LCD	LED	LCD	LED
Electrical Data	Voltage/frequency (V/Hz)	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz
	Rated Power (W)	105W	205W	125W	540W
	Current (A)	0.6A	1.37A	0.6A	3.5A
Material	Inside material	Pre-coated steel plate	Aluminum plate with spraying	Pre-coated steel plate	Cold-rolled steel plate
	Outside material	HIPS	PCM	HIPS	Stainless steel
	Insulation	Cyclopentane	PU Foam	Cyclopentane	Cyclopentane
Dimensions	Capacity (L)	R:138L,F:70L	R:174L, F:118L	R:160L,F:105L	R:188L,F:100L
	NT./GT. (kg)	63kg/73kg	87kg/95kg	60kg/65kg	146kg/175kg
	Exterior size(W*D*H)(mm)	541*611*1434mm	700*640*1826mm	575*641*1687mm	737*780*1860mm
	Interior size(W*D*H)(mm)	Refrigerator : 431*480*665mm Freezer : 389*445*502mm	Refrigerator: 600*510*657mm Freezer: 500*460*535mm	Refrigerator : 460*480*720mm Freezer : 405*460*692mm	Refrigerator : 588*552*630mm Freezer : 511*491*415mm
	Package size(W*D*H)(mm)	711*633*1500mm	760*740*1910mm	656*696*1739mm	815*850*2070mm
	High/low temperature	Y	Y	Y	Y
	Power Failure	N	N	N	N
	Sensor error	Y	Y	Y	Y
Alarm	Lower battery	N	N	N	N
	high ambient temperaturepower alarm	N	N	N	N
	USB datalog failure alarm	N	N	N	N
	Door ajar	Y (Only for Refrigerator)	Y	Y (Only for Refrigerator)	Y (Only for Refrigerator)
	Caster	Y	Y	Y	Y
	Shelf / drawer	R:3 ,F:0 / R:0 ,F:4	R:3 ,F:0 / R:0 ,F:3	R:3 ,F:0 / R:0 ,F:4	R:3 ,F:0/ R:1 ,F:2
Accessories	Door Lock with Key	N	Y	N	N
	Test hole	N	Y	N	Y
	Door with heater	N	N	N	Y (Only for Refrigerator)
	USB port	N	N	N	Y
	Printer	N	N	N	N

	BNCRF-26U289	BNCRF-40U289	BNCRF-26U450	BNCRF-40U450	BNCRF-26U519	BNCRF-40U519
	Upright	Upright	Upright	Upright	Upright	Upright
	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling	R: Force air cooling F: Directing cooling
	Auto	Auto	Auto	Auto	Auto	Auto
	R134a	R290a	R600a	R600a	R600a	R600a
	3.11kWh	3.76kWh	3.29kWh	4.95kWh	3.76kWh	3.86kWh
		≤55db	≤55db	≤55db	≤55db	≤55db
	16~32°C	16~32°C	16~32°C	16~32°C	16~32°C	16~32°C
	2~8°C,-10~-26°C	2~8°C,-10~-40°C	2~8°C,-10~-26°C	2~8°C,-10~-40°C	2~8°C,-10~-26°C	2~8°C,-10~-40°C
	Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor
	LED	LED	LED	LED	LED	LED
	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz
	295W	380W	314W	432W	382W	395W
	2.23A	2.54A	2.11A	3.05A	2.54A	2.72A
	Stainless steel	Stainless steel	Aluminum plate with spraying	Aluminum plate with spraying	Aluminum plate with spraying	Aluminum plate with spraying
	SPCC steel with powder coating	SPCC steel with powder coating	PCM	PCM	PCM	PCM
	PU Foam	PU Foam	PURF	PURF	PURF	PURF
	R:189L, F:100L	R:189L, F:100L	R:225L,F:225L	R:225L,F:225L	R:315L,F:204L	R:315L,F:204L
	146kg/160kg	146kg/160kg	144kg/156kg	146kg/159kg	185kg/205kg	185kg/205kg
	700*640*1828mm	700*640*1828mm	810*735*1960mm	810*735*1960mm	910*740*1972mm	910*740*1972mm
	Refrigerator: 600*510*710mm Freezer: 500*460*505mm	Refrigerator: 600*510*710mm Freezer: 500*460*505mm	Refrigerator: 650*570*627mm Freezer: 650*570*627mm	Refrigerator: 650*570*627mm Freezer: 650*570*627mm	Refrigerator : 750*610*740mm Freezer : 650*560*565mm	Refrigerator: 750*610*740mm Freezer: 650*560*565mm
	828*746*1924mm	828*746*1924mm	895*820*2046mm	895*820*2046mm	990*855*2062mm	990*855*2062mm
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Y	Y	Y	Y	Y	Y
	Optional	Optional	Optional	Optional	Optional	Optional

