

BS-3035 Zoom Stereo Microscope



BS-3035T1

BS-3035B2

BS-3035B3

BS-3035T4

We have 4 stands and binocular/trinocular head, the models are: BS-3035B1, BS-3035T1, BS-3035B2, BS-3035T2, BS-3035B3, BS-3035T3, BS-3035B4, BS-3035T4.

“B” means binocular, “T” means trinocular.

“1” means the stand with round base, without illumination.

“2” means the stand with square base, without illumination

“3” means the stand with round base, with transmitted and Incident illumination

“4” means the stand with square base, with transmitted and Incident illumination

Introduction

BS-3035 series Zoom Stereo Microscope offer sharp 3 D images with very competitive price. Optional auxiliary objectives, light source, stands and other accessories can fulfill different requirements.

Feature

1. Well-coated optical components, providing sharp and high contrast images and ensure large depth of field.
2. High quality optical system with zoom magnification 8×-50×, zoom ratio 1:6.3.
3. Various eyepieces, objectives and other accessories can meet different requirements.

Application

BS-3035 series stereo zoom microscope is of great value in a variety of applications such as circuit board repair, circuit board inspection, surface mount technology work, electronics inspection, coin collecting, gemology and gemstone setting, engraving, repair and inspection of small parts.

Specification

Item	Specification	BS-3035B3	BS-3035T4
Viewing Head	Binocular Head, Inclined at 45°, Interpupillary Distance 52-75mm	●	○
	Trinocular Head, Inclined at 45°, Interpupillary Distance 52-75mm, 30:70	○	●

	light distribution		
Eyepiece	Extra wide field eyepiece EW10×/22mm	●	●
	WF15×/16mm		
	WF20×/12.5mm		
Zoom Objective	0.8×-5×	●	●
Zoom Ratio	6.3:1	●	●
Working Distance	115mm	●	●
Auxiliary objective	2×, WD 45mm	○	○
	0.5×, WD 210mm		
Stage Plate	Frosted Glass Plate, Diameter 100mm	●	●
	White&Black round plate, Diameter 100mm	●	●
Focusing Unit	Coarse Focus Knob with tension adjustable, Moving range 100mm	●	●
Illumination	Incident Illumination 100V-240V/ LED	●	●
	Transmitted Illumination 100V-240V/ LED	●	●
Attachment	Photo Adapter (For Nikon, Canon, Olympus, Sony DSLR Cameras)		○
	0.5X C-mount Adapter		●
Package	1pc/carton, 36.5cm*31cm*52cm, 8.5kg	●	●

Note: ● Standard Outfit, ○ Optional